

## WMT-H1 Features:

Can wireless transmit PC's mirror or extended desktop to base unit.

Quick "WMT-H1" button to selection switcher the active signal of PC, less than 1s.

"WMT-H1" button can independently step in/out the source of PC.

Dual color LED, green indicates active source signal, red indicates power/link.

BYOM: Support USB devices such as USB speakerphone, USB camera over

WiFi sharing.

## WMT-H1 Specification

Technical Specifications	WMT-H1
Video Input Formats	Compliant with DP 1.2 for 1.62Gbps, 2.7Gbps ,5.4Gbps
	Compliant with DP 1.2 and eDP1.4
	Support DP 1, 2 , 4 lanes
	Over type C
HDCP	HDCP1.3
Video Input Resolution	VESA, maximum 2560x1440
Video input timing	1920x1080,1680x1050, 1600x900,1440x900,1400x1050,1366x768,1280x1024,1280x800,1280x720,1024x768,1920x1200,1600x1200, 2560x1440 @24 25, 30, 50,60 HZ
Video Output Formats	1 x Wireless
Audio Input Formats	DP 2CH PCM
Audio Output Formats	WIFI 11b/g/n/ac
USB Input	USB type C (USB 2.0 only)
Wireless transmission protocol	WIFI IEEE 802.11 a/g/n/ac
WIFI Frequency band	2.4 GHz & 5 GHz
WIFI Antenna	MIMO 2x2
WIFI Data rate	Up to 1200Mbps
Video Capacity	Wireless Transmission 1080P@ 60Hz, 2560x1440 30Hz
Distance	Typical : 35m without obstacle between WMT3- H and WMS
Button	Capacitive touch Key and vibration
Indicator	Green/ Red/color back-lit LED indicator
Round Unit Dimensions (L x H x R)	without cable: 65mm x 15mm x80mm with cable: L=190mm
Weight	~0.2lbs (~85g)
Surface finish	1~2mm plastic with matte black finish
Operating Temperature	-4° to + 113 ° F (-20° C to +45° C)
Storage Temperature	-4° to + 140° F (-20° C to to +60° C)
Power Consumption	3W (max.)

