

WMT-H1 Features:

Can wireless transmit PC's mirror or extended desktop to base unit.

Quick "WMT-C1" button to selection switcher the active signal of PC, less than 1s.

"WMT-C1" button can independently step in/out the source of PC.

Dual color LED, green indicates active source signal, red indicates power/link.

Support USB devices such as USB speakerphone, camera over WiFi sharing.

WMT-C1 Specification

| Technical Specifications | WMT-C1 |
|--------------------------------|----------------------------------------------------------------------------------------------------------------------------------|
| Video Input Formats | Compliant with DP 1.2 for 1.62Gbps, 2.7Gbps ,5.4Gbps |
| | Compliant with DP 1.2 and eDP1.4 |
| | Support DP 1, 2 , 4 lanes |
| | Over type C |
| HDCP | HDCP1.3 |
| Video Input Resolution | VESA, maximum 2560x1440 |
| Video input timing | 1920x1080,1680x1050, 1600x900,1440x900,1400x1050,1366x768,1280x1024,1280x800,1280x720,1024x768,1920x1200,1600x1200, 2560x1440 |
| | @24 25, 30, 50,60 HZ |
| Video Output Formats | 1 x Wireless |
| Audio Input Formats | DP 2CH PCM |
| Audio Output Formats | WIFI 11b/g/n/ac |
| USB Input | USB type C (USB 2.0 only) |
| Wireless transmission protocol | WIFI IEEE 802.11 a/g/n/ac |
| WIFI Frequency band | 2.4 GHz & 5 GHz |
| WIFI Antenna | MIMO 2x2 |
| WIFI Data rate | Up to 1200Mbps |
| Video Capacity | Wireless Transmission 1080P@ 60Hz, 2560x1440 30Hz |
| Distance | Typical : 35m without obstacle between WMT3- H and WMS |
| Button | Capacitive touch Key and vibration |
| Indicator | Green/ Red/color back-lit LED indicator |
| Round Unit Dimensions | without cable: 65mm x 15mm x80mm |
| (L x H x R) | with cable: L=190mm |
| Weight | ~0.2lbs (~85g) |
| Surface finish | 1~2mm plastic with matte black finish |
| Operating Temperature | -4° to + 113 ° F (-20° C to +45° C) |
| Storage Temperature | -4° to + 140° F (-20° C to to +60° C) |
| Power Consumption | 3W (max.) |

