

# TCV SEALS



## 1. Description

TCV is the standard oil seal which used for rotation axis. It is linked together with metal skeleton and rubber elastic layer. Mainly used for the working conditions of low pressure and high speed rotation.

## 2. Standard materials

FKM, NBR

## 3. Installation Dimensions

Inner Diam.	Outer Diam.	Height	Order No.
17	30	6	TCV17*30*6
17.46	28.58	5.7/6.3	TCV17.46*28.58*5.7/6.3
18	30	6	TCV18*30*6
18	35	9	TCV18*35*9
19	30	6	TCV19*30*6
19	35	6	TCV19*35*6
20	47	6	TCV20*47*6
22	35	6	TCV22*35*6
24	38	8	TCV24*38*8
25	35	6	TCV25*35*6
25	35	7	TCV25*35*7
28	40	6	TCV28*40*6
28.56	42	5.5	TCV28.56*42*5.5
28.575	50.8	6.35	TCV28.575*50.8*6.35
30	42	7	TCV30*42*7
30	48	6	TCV30*48*6
30	52	7	TCV30*52*7
34.92	52	6	TCV34.92*52*6
34.93	50.8	7.95	TCV34.93*50.8*7.95
35	47	6	TCV35*47*6
35	52	7	TCV35*52*7
35	54	6/5.5	TCV35*54*6/5.5
35	55	7	TCV35*55*7
35	57	8	TCV35*57*8
37	57	9	TCV37*57*9
38.1	57.15	7.95	TCV38.1*57.15*7.95
40	52	7	TCV40*52*7
40	55	7	TCV40*55*7
40	60	12	TCV40*60*12
40	62	7	TCV40*62*7
40	67	7	TCV40*67*7

# TCV SEALS



Inner Diam.	Outer Diam.	Height	Order No.
40	80	7	TCV40*80*7
42	62	7	TCV42*62*7
42	72	6.5	TCV42*72*6.5
43.5	63.5	7	TCV43.5*63.5*7
44.45	57.15	7.9	TCV44.45*57.15*7.9
44.45	60	7	TCV44.45*60*7
45	62	7	TCV45*62*7
45	63	8	TCV45*63*8
45	65	6	TCV45*65*6
45	65	7	TCV45*65*7
45	80	7	TCV45*80*7
47	62	8	TCV47*62*8
49.23	63.55	7.95	TCV49.23*63.55*7.95
50	65	7	TCV50*65*7
50	68	7	TCV50*68*7
50	70	7	TCV50*70*7
50	72	7	TCV50*72*7
50	75	8	TCV50*75*8
50	80	7	TCV50*80*7
52	72	7/8	TCV52*72*7/8
55	70	7	TCV55*70*7
55	72	8	TCV55*72*8
55	78	8	TCV55*78*8
55	90	7	TCV55*90*7
58	80	8	TCV58*80*8
60	80	7	TCV60*80*7
62	85	7	TCV62*85*7
65	97	7.5	TCV65*97*7.5
70	95	7	TCV70*95*7
73	90	7/8	TCV73*90*7/8
80	100	7	TCV80*100*7
60	106	7	TCV60*106*7
85	110	8	TCV85*110*8
90	110	7	TCV90*110*7
75	120	7	TCV75*120*7
100	120	8	TCV100*120*8