



WIRE MESH SHOT BLASTING MACHINE

- SPECIAL FOR SMALL SIZE FORGINGS, HEAT TREATMENT, CUTTING & WELDING PARTS



KHOLEE BLASTING ENGINEERING CO., LTD

EXPERT IN BLASTING & PAINTING INDUSTRY

| DALONG INDUSTRIAL PARK, DAFENG, YANCHENG, JIANGSU, CHINA 224125

| EMAIL: KHOLEEBLAST@GMAIL.COM | WEBSITE: WWW.KHOLEEBLASTING.COM


| CARL CHEN | WHATSAPP/MOBILE: +86-139 1469 8671

WIRE MESH BELT SHOT BLASTING MACHINE

Wire mesh shot blasting machine is used in large quantities of small parts and thin-wall castings, thin-wall and fragile iron or aluminum ally castings, ceramic, and other workpiece surface cleaning. Placing several small workpieces side by side on the wire mesh belt can significantly increase the machine throughput. Standard transport speeds vary between 0.6-6 m/min. When the workpieces pass through shot blasting area, rust, dust, oxide layers or sand, burr will be removed. With machine widths from 600 to 1,500 mm the wire mesh shot blasting machine can practically handle any work piece size and throughput with minimum space requirements.

The equipment is comprised of stainless wire mesh conveyor, shot blasting chamber, blasting turbine, shots recycle system, shots clean off system, dust removing system, out-feeding roller conveyor and electrical control system etc.

| WIRE MESH SHOT BLASTING MACHINE | | | | | | | | |
|---------------------------------|-----------|-----------|----------------|------------|--|--|--|--|
| Model | KLWD600-4 | KLWD800-4 | KLWD1000-4 | KLWD1000-8 | | | | |
| Wire Mesh Width | 600mm | 800mm | 1000mm | | | | | |
| Max Products Size (W×H) | 500×500mm | 700×500mm | 900×500mm | | | | | |
| Max Products Weight | 100 | 0kg | 200kg | | | | | |
| Max Loading | 600kgs | 800kgs | 1000kgs | | | | | |
| Blasting Turbine | 7.5kw×4 | 7.5kw×4 | 11kw×4 7.5kw×8 | | | | | |
| Dust Air Volume | 12500 | Dm³/hr | 15000m³/hr | | | | | |
| Foundation Pit | N | lo | Yes | | | | | |





Note:

- KHOLEE BLAST ALSO DESIGNS AND MANUFACTURES NON-STANDARD WIRE MESH SHOT BLASTING MACHINE ACCORDING TO CLIENTS' REQUIREMENTS AND WORK-PIECES SIZE.
- WE HAVE THE POLICY TO IMPROVE OUR EQUIPMENT CONTINUOUSLY & SHALL RESERVE THE RIGHTS TO CHANGE THE DIMENSIONS AND SPECS WITHOUT PRIOR NOTICE.

KHOLEE BLASTING ENGINEERING CO., LTD • Blasting & Painting Solutions

Dalong Industrial Park, Dafeng, Yancheng, Jiangsu, China • 221425

© 2017 Kholeeblast - Doc.nr.KL1004 Rev.A Sep 2017

Tel: +86-515-8380 9688 • Fax: +86-515-83755498

Printed in Yancheng China

Email: kholeeblast@gmail.com ● Web: www.kholeeblasting.com ● The right is reserved to make changes at any time without notice

| WIRE MESH SHOT BLASTING MACHINE | | | | | | | | | |
|---------------------------------|---------------|------------|------------|------------|--|--|--|--|--|
| Model | KLWD1250-4 | KLWD1250-8 | KLWD1500-4 | KLWD1500-8 | | | | | |
| Wire Mesh Width (mm) | 1250mm 1500mm | | | | | | | | |
| Max Products Size (W×H) | 1100× | 500mm | 1400×500mm | | | | | | |
| Max Products Weight | 20 | 0kg | 200kg | | | | | | |
| Max Loading | 120 | 0kgs | 1500kgs | | | | | | |
| Blasting Turbine | 11kw×4 | 7.5kw×8 | 11kw×4 | 7.5kw×8 | | | | | |
| Dust Air Volume | 15000 | Om³/hr | 15000m³/hr | | | | | | |
| Foundation Pit | Yes Yes | | | | | | | | |



Note:


- KHOLEE BLAST ALSO DESIGNS AND MANUFACTURES NON-STANDARD WIRE MESH SHOT BLASTING MACHINE ACCORDING TO CLIENTS' REQUIREMENTS AND WORK-PIECES SIZE.
- WE HAVE THE POLICY TO IMPROVE OUR EQUIPMENT CONTINUOUSLY & SHALL RESERVE THE RIGHTS TO CHANGE THE DIMENSIONS AND SPECS WITHOUT PRIOR NOTICE.





HIGH QUALITY STEEL SHOT & STEEL GRIT

MEATAL ABRASIVES FOR WIRE MESH SHOT BLASTING MACHINE WORKING



KHOLEE BLASTING ENGINEERING CO., LTD


EXPERT IN BLASTING & PAINTING INDUSTRY

| DALONG INDUSTRIAL PARK, DAFENG, YANCHENG, JIANGSU, CHINA 224125

| EMAIL: KHOLEEBLAST@GMAIL.COM | WEBSITE: WWW.KHOLEEBLASTING.COM

| CARL CHEN | WHATSAPP/MOBILE: +86-139 1469 8671

HT Abrasives, one of three companies in China have two quenching equipment, has the capacity to produce high quality steel shots and grits. KHOLEE BLAST, as a GOLDEN Distributor of HT metal abrasives in China, assists our clients to select the right steel shots & grits and analyzing the working max and production process in order to maximize the efficiency. All our steel shots & grits are subject to a rigorous quality control to ensure supply the best available abrasives in its class.



KHOLEE BLASTING ENGINEERING CO., LTD • Blasting & Painting Solutions

Dalong Industrial Park, Dafeng, Yancheng, Jiangsu, China ● 221425

© 2017 Kholeeblast - Doc.nr.KL1004 Rev.A Sep 2017

Tel: +86-515-8380 9688 • Fax: +86-515-83755498

Printed in Yancheng China

Email: kholeeblast@gmail.com • Web: www.kholeeblasting.com

• The right is reserved to make changes at any time without notice

Operative Standards:

In accordance with standards of GB/T18838.3 – 2008 Steel Shot and Steel Grit, SFSA20-66Cast Steel Abrasive, SAE J827 Cast Steel Shot, SAE J1993High Carbon Steel Grit, YB/T5149-1993 Cast Steel Shot, YB/T5150-1993Cast Steel Grit, ISO11124-3High Carbon Cast Steel Shot and Grit.

| Steel Shot \$780/\$\$2.5 \$660/\$\$2.0 | Steel Grit G10/SG2.5 G12/SG2.0 | Application Sand removal of large sized castings, scale removal of large sized products from forging, stamping, die forging, drawing and rolling or after heat treatment (e.g. pipes, sections, plates, fittings, wire). |
|--|--------------------------------------|---|
| S550/SS1.7 S460/SS1.4 | G14/SG1.7 G16/SG1.4 | Sand removal of large and medium sized castings, scale removal of forging and heat-treated work pieces, surface blast cleaning of steel plates, sections and steel structures, shot peening of work pieces, cutting of granite. |
| S390/SS1.2 S330/SS1.0 | G18/SG1.2 G25/SG1.0 | Sand removal of medium and small sized castings, surface blast cleaning of forgings, heat-treated pieces, steel pipes, sections and steel structures, surface treatment before painting, shot peening of work pieces. |
| S280/SS0.8 S230/SS0.6 | G25/SG1.0 G40/SG0.7 | Surface blast cleaning of small sized castings, forgings and heat-treated pieces, aluminium and copper alloy castings, steel plates, steel pipes, sections and steel structures, shot peening of work pieces. |
| \$170/\$\$0.5 \$110/\$\$0.3 | G50/SG0.4 G80/SG0.3 G120/SG0.2 | Surface blast cleaning of stainless steel plates, thin steel plates, non-ferrous alloys, dacromet coat. |

Application Equipment

Shot Blasting Machine (Auto Wheel Blasting Machine)

Steel Plate Shot Blasting Machine | Steel Structure Shot Blasting Machine | Steel Pipe Shot Blasting Machine | Hanger Type Shot Blasting Machine | Turntable Shot Blasting Machine | Tumble Belt Shot Blasting Machine | Overhead Conveyor Shot Blasting Machine | Steel Cylinder Shot Blasting Machine | Trolley Type Shot Blasting Machine | Wire Mesh Shot Blasting Machine etc.

- Blasting Room
- Sand Blasting Machine, Blasting Pot
- Shot Peening Machine

KHOLEE BLASTING ENGINEERING CO., LTD • Blasting & Painting Solutions

| | Specifi | cation of High Q | uality Steel Shots | | | | | | | |
|---------------------------|------------|--|-----------------------|------------------------|--------|--|--|--|--|--|
| Item | С | Si | Mn | S | Р | | | | | |
| HQ Steel Shots | 0.85-1.20% | 0.40-1.20% | 0.60-1.20% | <0.05% | <0.05% | | | | | |
| Hardness | | 40 ~ 50HRC 52 ~ 56HRC 56 ~ 60HRC, Max Deviation ±3.0 HRC | | | | | | | | |
| Density | | | 7.4 g/cm ³ | | | | | | | |
| Bulk Density | | | 4.4 g/cm ³ | | | | | | | |
| Ervin Cycle Times | | | 2800~3300 times | S | | | | | | |
| Micro-Structure | | Homogene | ous Tempered Marte | nsite or Troostite | | | | | | |
| Color | | | Dark Black | | | | | | | |
| Size of HQ Steel Shots | | \$780. \$660 \$330 \$280 | | 460 \$390 170 \$110 | | | | | | |

| | | | | Dist | ribution | of High C | Quality St | eel Shots | 3 | | | |
|------|-------|--------------------------------|----------|----------|----------|-----------|------------|-----------|----------|----------|----------|----------|
| | | Specification of Steel Shot mm | | | | | | | | | | |
| Mesh | mm | SS-2.5 | SS-2.0 | SS-1.7 | SS-1.4 | SS-1.2 | SS-1.0 | SS-0.8 | SS-0.6 | SS-0.5 | SS-0.3 | SS-0.2 |
| 7 | 2.80 | all pass | | | | | | | | | | |
| 8 | 2.36 | | all pass | | | | | | | | | |
| 10 | 2.00 | 85%min | | all pass | all pass | | | | | | | |
| 12 | 1.70 | 97%min | 85%min | | 5%max | all pass | | | | | | |
| 14 | 1.40 | | 97%min | 85%min | | 5%max | all pass | | | | | |
| 16 | 1.18 | | | 97%min | 85%min | | 5%max | all pass | | | | |
| 18 | 1.00 | | | | 96%min | 85%min | | 5%max | all pass | | | |
| 20 | 0.850 | | | | | 96%min | 85%min | | 10%max | all pass | | |
| 25 | 0.710 | | | | | | 96%min | 85%min | | 10%max | | |
| 30 | 0.600 | | | | | | | 96%min | 85%min | | all pass | |
| 35 | 0.500 | | | | | | | | 97%min | 85%min | 10%max | |
| 40 | 0.425 | | | | | | | | | 97%min | | all pass |
| 45 | 0.355 | | | | | | | | | | 80%min | 10%max |
| 50 | 0.300 | | | | | | | | | | 90%min | |
| 80 | 0.180 | | | | | | | | | | | 80%min |
| 120 | 0.125 | | | | | | | | | | | 90%min |
| 200 | 0.075 | | | | | | | | | | | |
| 325 | 0.045 | | | | | | | | | | | |
| SA | λE | S-780 | S-660 | S-550 | S-460 | S-390 | S-330 | S-280 | S-230 | S-170 | S-110 | S-70 |

KHOLEE BLASTING ENGINEERING CO., LTD • Blasting & Painting Solutions

Dalong Industrial Park, Dafeng, Yancheng, Jiangsu, China • 221425

© 2017 Kholeeblast - Doc.nr.KL1004 Rev.A Sep 2017

Tel: +86-515-8380 9688 • Fax: +86-515-83755498

Printed in Yancheng China

Email: kholeeblast@gmail.com • Web: www.kholeeblasting.com • The right is reserved to make changes at any time without notice

| | Specification of High Quality Steel Grits | | | | | | | | | |
|---------------------------|---|------------|-----------------------|------------------------|--------|--|--|--|--|--|
| Item | С | Si | Mn | S | Р | | | | | |
| HQ Steel Grits | 0.85-1.20% | 0.40-1.20% | 0.60-1.20% | <0.05% | <0.05% | | | | | |
| Hardness | GP: 42 ~ 50HRC GL: 56 ~ 60HRC GH: 63 ~ 66HRC Max Deviation ±3.0 HRC | | | | | | | | | |
| Density | | | 7.6 g/cm ² | 3 | | | | | | |
| Bulk Density | | | 4.2 g/cm ² | 3 | | | | | | |
| Micro-Structure | | Homogene | eous Tempered Ma | artensite or Troostite | | | | | | |
| Color | | GP, | GL: Dark Black G | GH: Light Black | | | | | | |
| Size of HQ Steel Grits | | G10 G3 | | G16 G18 | | | | | | |

| | | Specification of Steel Grit mm | | | | | | | | | | |
|------|-------|--------------------------------|----------|----------|----------|----------|----------|----------|----------|----------|----------|--|
| Mesh | mm | 2.5 | 2.0 | 1.7 | 1.4 | 1.2 | 1.0 | 0.7 | 0.4 | 0.3 | 0.2 | |
| 7 | 2.80 | all pass | | | | | | | | | | |
| 8 | 2.36 | | all pass | | | | | | | | | |
| 10 | 2.00 | 80%min | | all pass | | | | | | | | |
| 12 | 1.70 | 90%min | 80%min | | all pass | | | | | | | |
| 13 | 1.40 | | 90%min | 80%min | | all pass | | | | | | |
| 16 | 1.18 | | | 90%min | 75%min | | all pass | | | | | |
| 18 | 1.00 | | | | 85%min | 75%min | | all pass | | | | |
| 20 | 0.850 | | | | | | | | | | | |
| 25 | 0.710 | | | | | 85%min | 70%min | | all pass | | | |
| 30 | 0.600 | | | | | | | | | | | |
| 35 | 0.500 | | | | | | 80%min | | | | | |
| 40 | 0.425 | | | | | | | 70%min | | all pass | | |
| 45 | 0.355 | | | | | | | | | | | |
| 50 | 0.300 | | | | | | | 80%min | 65%min | | all pass | |
| 80 | 0.180 | | | | | | | | 75%min | 65%min | | |
| 120 | 0.125 | | | | | | | | | 75%min | 60%min | |
| 200 | 0.075 | | | | | | | | | | 70%min | |
| 325 | 0.045 | | | | | | | | | | | |
| S | AE | G-10 | G-12 | G-14 | G-16 | G-18 | G-25 | G-40 | G-50 | G-80 | G-120 | |

Packaging

- 25kgs /bag, 40 bags in big bag or 80 bags in big bag
- 1000 kgs in big bag

KHOLEE BLASTING ENGINEERING CO., LTD • Blasting & Painting Solutions

Dalong Industrial Park, Dafeng, Yancheng, Jiangsu, China ● 221425

© 2017 Kholeeblast - Doc.nr.KL1004 Rev.A Sep 2017

Tel: +86-515-8380 9688 • Fax: +86-515-83755498

Printed in Yancheng China

Email: kholeeblast@gmail.com • Web: www.kholeeblasting.com

• The right is reserved to make changes at any time without notice