


Polycrystalline solar panel PVS-335W/340W-72P



PVSY ENERGY GROUP LIMITED is the professional manufacturer of solar panel, solar system and solar lighting.

We are not only offer these solar products, but also offer the whole complete solar system to our customers. With our professional solution and best offer, customers can save their total cost of the whole solar system.


We made our system in modularity, it is easy for our customers to maintain the system and it is easy for us to offer the best after sales service.

Redefined the high-efficiency module series by integrating 156.75mm silicon wafers with multi-busbar cell technologies. Our panel combined creative technology effectively and extremely improved the module efficiency and power output.

● KEY FEATURES

- Less mismatch to get more power
- Less power loss by minimizing the shading impact
- Competitive low light performance
- 3 times EL test to ensure best quality
- Ideal choice for utility and commercial scale projects by reduced BoS and improved ROI
- PVEL Outstanding reliability proven by PVEL for stringent environment condition:
 - Sand, acid, salt, and hail stones
 - 2400 Pa wind load and 5400 Pa snow load
 - Anti-PID

● WARRANTY



15 YEARS Guarantee on product material and workmanship

25 YEARS Linear power output warranty

Electrical Characteristics:

Module Type	PVS-335W-72P	PVS-340W-72P
Maximum Power (Pmp)	335	340
Open Circuit Voltage (Voc)	45.89	45.99
Short Circuit Current (Isc)	9.25	9.47
Maximum Power Voltage (Vmp)	38.90	38.97
Maximum Power Current (Imp)	8.63	8.73
Module Efficiency at STC(η_m)	17.26	17.52
Power Tolerance	(0,+3%)	
Maximum System Voltage	1500VDC	
Maximum Series Fuse Rating	25A	
STC: Irradiance 1000 W/m ² module temperature 25°C AM=1.5		

Temperature Characteristics:

Pmax Temperature Coefficient	-0.35 %/°C
Voc Temperature Coefficient	-0.27 %/°C
Isc Temperature Coefficient	+0.05 %/°C
Operating Temperature	-40~+85 °C
NOCT	45±2 °C

Mechanical Specifications:

External Dimensions	1956x992x35 mm
Weight	22kg
Solar Cells	Poly (72pcs)
Front Glass	3.2mm tempered glass
Frame	Anodized aluminium alloy
Junction Box	IP68, 3 diodes
Output Cables	4.0mm ² 1000mm
Mechanical Load	Front side 5400Pa Rear side 2400Pa

Packing Configuration:

Container	20'GP	40'HQ
Pieces per Container	310	818

