

PERC MONOCRYSTALLINE SOLAR PANEL PVS-410W/420W-M10H



Introduction:

Redefined the high-efficiency module series by integrating 182mm silicon wafers with PERC cell technologies. Our panel combined creative technology effectively and extremely improved the module efficiency and power output.


Key Features:

- Less mismatch to get more power
- Less power loss by minimizing the shading impact
- Competitive low light performance
- 3 times EL test to ensure best quality
- Anti-PID
- Ideal choice for utility and commercial scale projects by reduced BoS and improved ROI
- Outstanding reliability proven by PVEL for stringent Environment condition: Sand, acid, salt and hail stones, 2400Pa wind load and 5400Pa snow load

Electrical Characteristics: STC: Irradiance 1000 W/m² module temperature 25 C AM=1.5


Module Type	PVS-410W-M10H	PVS-420W-M10H
Maximum Power (Pmp)	410W	420W
Open Circuit Voltage (Voc)	37.50V	37.90V
Short Circuit Current (Isc)	13.84A	13.97A
Maximum Power Voltage (Vmp)	31.30V	31.70V
Maximum Power Current (Imp)	13.10A	13.26A
Module Efficiency at STC(%)	22.37%	22.53%
Maximum System Voltage	1500VDC	
Maximum Series Fuse Rating	25A	
Power Tolerance	0~+3%	

Current-Voltage Characteristic (I-V Curve)



Mechanical Specifications:

External Dimensions	1722x1134x30mm
Solar Cells	Mono 108cells
Front Glass	3.2mm tempered glass
Frame	Anodized aluminum alloy
Junction Box	IP68, 3 diodes
Output Cables	4.0mm ²
Weight	22kg
Mechanical Load	Front side 5400Pa Rear side 2400Pa
Packing	36pcs/pallet, 936pcs/40HQ



Product warranty:

15 years guarantee on product material and workmanship
 25 years guarantee on Liner power output

Quality Standard: IEC61215-1-1:2021, IEC61730-1 :2018, IEC61730-2:2018, Fire safety Class C

Temperature ratings (STC):

Temperature Coefficient of Isc	+0.040%/°C
Temperature Coefficient of Voc	-0.270%/°C
Temperature Coefficient of Pmax	-0.350%/°C